

ROMESS® S30-60



Since 1970 Romess devices comply with the requirements of international car manufacturers
The ROMESS S 30-60 has received official approval and recommendations from the following makers:

Daimler – Ford – BMW – Opel – Porsche – Renault



Mobile Brake Maintenance Unit for
30 to 60 liter containers DOT brake fluid
For all passenger cars, trucks and motorcycles
For all ABS-, ESP-, EDS- and SBC-Systems

Brake maintenance unit
S 30-60



Application:

The brake maintenance unit S 30-60 is the ideal unit for service centers with more than 10 brake fluid changes per day. The unit can be easily managed by just one person which saves valuable time and money. The high flow pressure guarantees a complete flush and bleed of the hydraulic or clutch systems and thus ensures functional reliability of the brake and ABS systems.

Seals of approval from

Daimler

Design and function:

The S 30-60 is a solid, mobile brake maintenance unit designed for using original, commercial-type 30 – 60 liter canisters of brake fluid. The light aluminum and steel construction supported by two rubber wheels and 2 swivel castors make the device easy to transport and manage, even with a full canister. The pressure is adjustable from 0.4 to 3.5 (6 to 51 psi). The average working pressure is 1.5 to 2.5 bar (22 to 36 psi) - refer to vehicle manufacturer for specifications. The integrated shut-off valve allows a leakage test to be performed after repair of the brake or clutch system.

Ford

Characteristics:

- ★ for all commercial vehicles
- ★ one-man-operation (no special instructions needed)
- ★ for anti-lock braking systems (ABS)
- ★ no compressed air
- ★ quick-lock coupling
- ★ automatic shut-off on minimum level
- ★ complete flush and bleed of the hydraulic system

BMW

Opel

Technical data:

- ★ CE-certified, protection IP43
- ★ Power supply: 110V/60 Hz + 16 foot power cord with safety plug.
- ★ Pressure: adjustable from approx. 6 to 51 psi (0.4 to 3.5 bar)
- ★ working pressure commonly 22 to 36 psi (1.5 to 2.5 bar)
- ★ Pressure gauge: range 0 to 87 psi (0 to 6 bar)
- ★ Measurements (in inches): L x W x H: 17 x 18 x 34.5, weight approx. 44 lbs
- ★ Packing measurements (in inches): L x W x H: 25 x 19 x 33, weight approx. 48.5 lbs
- ★ Scope of delivery:
Brake maintenance device with filling hose and standard adapter 50232
for most vehicles, pre-draining system with catch bottle 50273

Porsche

Renault