

*Lifting Britain since 1896*

## WC5301 Tyre Changer Machine (1 Phase)

### Product Description

The Bradbury WC5301 single phase fully automatic tyre changer machine is suitable for wheels up to 26" (clamping on the outside) or 23" (clamping on the inside).

This tyre machine can be fitted with an assist arm (also known as a third arm) to aid the user with changing low profile and run flat tyres (WCAA optional extra)

All Bradbury tyre machines are built up and tested in our UK facility prior to being sent out.

CE Approved



### Technical Specifications

Clamping capacity (outside / rim diameter)	12" – 23"
Clamping capacity (inside diameter)	14" – 26"
Rim width	3"–13"
Maximum wheel diameter	1040 mm
RPM	7 RPM
Operating pressure	8 – 10BAR
Air required	Yes
Bead breaker force	2,800kg
Electrical supply	220 / 240 Volt (1 phase)
Size of demount shaft	41 mm
Size of slider arm	55 mm

### Optional Extras

- DTMPKIT - Starter Kit
- ST-4/KH - Quick release demount head with plastic mounting head tool.
- QT-20 - Plastic protector for tyre lever



GEMCO Sales & Service, 153-165 Bridge St, Northampton, NN1 1QG



LinkedIn: GEMCO Sales & Service Facebook: GEMCO Sales & Service Twitter: @GemcoEquipment

Specifications/Images subject to change without prior notice. E&OE Images are for illustration purposes only. To validate warranty, proof of a valid maintenance contract will be required.

