



Since 1970 Romess devices comply with the requirements of international car manufacturers



One-man operation
For original one gallon canisters
Compartment for tools and accessories

Brake maintenance unit
BW 1408



Application:

The portable brake maintenance unit **BW 1408** was developed for use with one gallon original, commercial-type canisters of brake fluid. No decanting necessary. As an option, the **BW 1408** is available with an integrated refill tank. The compact size makes it ideal for mobile use on the go.

Design and function:

The durable and padded handle makes transport easy - even with a full container. When the canister is empty, a preset pressure switch set automatically deactivates the unit to avoid air being accidentally pumped into the hydraulic system.

The unit is also available with an integrated 1.5 gallon tank.

Also available – the **BW 1408** as **Duo version** with integrated pre-draining system for emptying the vehicle compensation reservoir.

Characteristics:

- ★ for anti-lock braking systems (ABS)
- ★ one-man operated (no special instructions needed)
- ★ no compressed air
- ★ quick lock coupling
- ★ automatic deactivation of the pump on empty container, insufficient pressure or air in the supply hose
- ★ complete flush + bleed of the hydraulic system

Technical data:

- ★ CE marking, protection IP43
- ★ Power supply: 110V/60 Hz plus 16 foot power cord with safety plug
- ★ Pressure: adjustable from 0 to 2.8 bar (working pressure commonly 1.5 to 2.5 bar)
- ★ Pressure gauge: range 0 to 6 bar
- ★ Measurements: L x W x H in inches: 17 x 14 x 16, weight: 13 lbs
- ★ Packing measurements: L x W x H in inches: 20 x 15 x 19, weight: 15 lbs
- ★ Scope of delivery:
Brake maintenance device with filling hose and standard adapter 50232 for most vehicles

1418	BW 1408 A with pre-draining system	BW 1408 B standard	BW 1408 T with tank
110V / 60Hz	1408	1409	1410