



Compressed air at your service



## PRO Series Direct drive & belt driven piston compressors

ABAC PRO direct drive units offer a user friendly, reliable and sturdy design. Belt driven units are equipped with the best belt guard available, providing an optimal air flow over the pump. The pumps are running at lower speed and all come with aftercoolers to reduce operating temperatures even more than ever before. All machines have the maximum number of feet with rubber bumpers or lockable pivot wheels, providing the safest and best stability possible.

## **Applications**













## **Efficiency**

Highly innovative belt guard streamlining and improving the cooling air flow over the pump

## **Durability**

Standard aftercooler on the highly durable and newly developed slow running pump



User comfort
With extra rubber
handles and lockable
pivot wheels

_			<b>=</b>			H			7		M	
Model	Partnumber	L	Pump	l/min	CFM	HP	kW	rpm	Volt	Bar	L x W xH (mm)	Kg
START O20P UK	4116023493	6	Oil Free	230	8.1	2	1.5	2850	230/1/50	8	535 x 215 x 535	15.9
POLE POSITION 020P	4116023494	24	Oil Free	230	8.1	2	1.5	2850	230/1/50	8	570 x 250 x 590	24.5
POLE POSITION L30P	4116023501	24	Lubricated	310	10.9	3	2.2	2850	230/1/50	10	570 x 255 x 590	33
MONTECARLO 020P	4116023495	50	Oil Free	230	8.1	2	1.5	2850	230/1/50	8	770 x 310 x 645	30.5
MONTECARLO L30P	4116023502	50	Lubricated	310	10.9	3	2.2	2850	230/1/50	10	770 x 310 x 645	36.5
ESTORIL L30P	4116023503	90	Lubricated	310	10.9	3	2.2	2850	230/1/50	10	1060 x 385 x 730	48
PRO A29B 50 CM2	4116024556	50	A29B	255	8.9	2	1.5	1075	230/1/50	10	870 x 370 x 780	49
PRO A39B 90 CM3	4116024523	90	A39B	393	13.8	3	2.2	1050	230/1/50	10	1180 x 460 x 930	72
PRO A39B 150 FM3	4116024538	150	A39B	393	13.8	3	2.2	1050	230/1/50	10	1375 x 420 x 950	87
PRO A39B 150 FT3	4116024539	150	A39B	393	13.8	3	2.2	1050	400/3/50	10	1375 x 420 x 950	87
PRO A39B 200 FM3	4116024540	200	A39B	393	13.8	3	2.2	1050	230/1/50	10	1500 x 470 x 1110	91
PRO A39B 200 FT3	4116024541	200	A39B	393	13.8	3	2.2	1050	400/3/50	10	1500 x 470 x 1110	91
PRO B4900 200 FT4	4116019576	200	B4900	514	18	4	3	1400	400/3/50	11	1500 X 450 X 960	137
PRO B5900B 200 FT5.5	4116019700	200	B5900	653	22,9	5.5	4	1400	400/3/50	11	1580 X 580 X 1150	161
PRO B6000 270 FT7.5	4116020190	270	B6000	827	28.9	7.5	5.5	1400	400/3/50	11	1520 X 600 X 1250	177
PRO B7000 270 FT10	4116020790	270	B7000	1210	42.4	10	7.5	1300	400/3/50	11	1520 X 600 X 1250	196



